

Description

Fastener Length: 3/4", Thread: 1/4-20, Head Width: 1/8", Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS5104554 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-071-8821 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS51045-54 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.750 Inches Minimum |
| Fastener Length: | 0.750 Inches Nominal |
| Head Style: | Headless (setscrew) |
| Point Style: | Half Dog |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.250 Inches |
| Width Across Flats: | 0.125 Inches Nominal |
| Thread Quantity Per Inch: | 20 |
| Hardness Rating: | 25.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Material: | Steel Corrosion Resisting Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this set screw from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/MS51045-54> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.