

## P/N MS51095-307

## **Description**

Fastener Length: 55/64", Hole Diameter: 1/16", Thread: 1/4-20, Thread Length: 7/8"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS51095307

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-916-6465

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS51095-307 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Maximum
Fastener Length:	0.845 Inches Minimum And 0.875 Inches Maximum
Head Style:	Hexagon
Head Height:	0.150 Inches Minimum And 0.163 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.438 Inches Maximum
Hole Diameter:	0.062 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	120000 Pounds Per Square Inch
Hardness Rating:	23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Flats
Material:	Steel Overall
Material Document And Classification:	Sae Gr 5 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

### **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS51095-307">https://military-fasteners.com/screws/machine+screws/MS51095-307</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.