



Military-Fasteners.com

P/N MS51095-412L

Description

Fastener Length: 0-31/32", Hole Diameter: 3/32", Thread: 1/2-13, Thread Length: 0-25/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS51095412L
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-210-9421
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS51095-412L Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.777 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	0.969 Inches Minimum And 1.000 Inches Maximum
Head Style:	Hexagon
Head Height:	0.302 Inches Minimum And 0.323 Inches Maximum
Width Between Flats:	0.736 Inches Minimum And 0.750 Inches Maximum
Hole Diameter:	0.092 Inches Minimum And 0.100 Inches Maximum
Locking Feature:	Patch Threads Or Strip Threads
Nominal Thread Diameter:	0.500 Inches
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	13
Minimum Tensile Strength:	120000 Pounds Per Square Inch
Hardness Rating:	25.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Material:	Steel Comp 1013 Overall Or Steel Comp 1015 Overall Or Steel Comp 1016 Overall Or Steel Comp 1017 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1020 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1023 Overall Or Steel Comp 1524 Overall Or Steel Comp 1025 Overall Or Steel Comp 1026 Overall Or Steel Comp 1527 Overall Or Steel Comp 1029 Overall Or Steel Comp 1030 Overall Or Steel Comp 1033 Overall Or Steel Comp 1034 Overall Or Steel Comp 1035 Overall Or Steel Comp 1536 Overall Or Steel Comp 1037 Overall Or Steel Comp 1038 Overall Or Steel Comp 1039 Overall Or Steel Comp 1040 Overall Or Steel Comp 1541 Overall
Surface Treatment:	Cadmium Overall Or Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS51095-412L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.