

Description

Fastener Length: 1-15/16", Thread: 1/2-13, Thread Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS51095416L |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-112-7869 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS51095-416L Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.250 Inches Minimum And 1.442 Inches Maximum |
| Fastener Length: | 1.938 Inches Minimum And 2.000 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.302 Inches Minimum And 0.323 Inches Maximum |
| Width Between Flats: | 0.736 Inches Minimum And 0.750 Inches Maximum |
| Locking Feature: | Patch Threads Or Pellet Threads Or Strip Threads |
| Nominal Thread Diameter: | 0.500 Inches |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 13 |
| Minimum Tensile Strength: | 120000 Pounds Per Square Inch |
| Hardness Rating: | 25.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 1013 Overall Or Steel Comp 1015 Overall Or Steel Comp 1016 Overall Or Steel Comp 1017 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1020 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1023 Overall Or Steel Comp 1524 Overall Or Steel Comp 1025 Overall Or Steel Comp 1026 Overall Or Steel Comp 1527 Overall Or Steel Comp 1029 Overall Or Steel Comp 1030 Overall Or Steel Comp 1033 Overall Or Steel Comp 1034 Overall Or Steel Comp 1035 Overall Or Steel Comp 1536 Overall Or Steel Comp 1037 Overall Or Steel Comp 1038 Overall Or Steel Comp 1039 Overall Or Steel Comp 1040 Overall Or Steel Comp 1541 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 2 Type And 10p Style And 5 Grade |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS51095-416L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.