

Description

Fastener Length: 0-63/64", Hole Diameter: 3/32", Thread: 1/2-20, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS51096412
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-939-1176
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS51096-412 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.812 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	0.970 Inches Minimum And 1.000 Inches Maximum
Head Style:	Hexagon
Head Height:	0.302 Inches Minimum And 0.323 Inches Maximum
Width Between Flats:	0.736 Inches Minimum And 0.750 Inches Maximum
Hole Diameter:	0.094 Inches Nominal
Nominal Thread Diameter:	0.500 Inches
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	120000 Pounds Per Square Inch
Hardness Rating:	23.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Flats
Material:	Steel Overall
Material Document And Classification:	Sae Gr 5 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS51096-412> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.