



Military-Fasteners.com

P/N MS51099-34

Description

Fastener Length: 0-31/32", Hole Diameter: 1/16", Thread: 5/16-18, Thread Length: 25/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5109934
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-045-2861
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS51099-34 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.781 Inches Minimum
Fastener Length:	0.969 Inches Minimum And 1.000 Inches Maximum
Head Style:	Hexagon
Head Height:	0.195 Inches Minimum And 0.211 Inches Maximum
Width Between Flats:	0.489 Inches Minimum And 0.500 Inches Maximum
Hole Diameter:	0.062 Inches Nominal
Nominal Thread Diameter:	0.312 Inches
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	70000 Pounds Per Square Inch
Minimum Yield Strength:	40000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Longitudinal Hole
Surface Finish:	32.0 Microinches Threads
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	66,400 Series Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	2 Type And 10p Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51099-34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.