

# P/N MS51100-37

## **Description**

Fastener Length: 1-3/4", Thread: 5/16-24, Thread Length: 7/8"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS5110037

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-485-8083

National Motor Freight: 096640, Screws, Iron Or Steel



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS51100-37 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.874 Inches Nominal
Fastener Length:	1.750 Inches Nominal
Head Style:	Hexagon
Head Height:	0.195 Inches Minimum And 0.211 Inches Maximum
Width Between Flats:	0.4890 Inches Minimum And 0.5000 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Special Features:	The Head Is Drilled For A Lockingwire
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ff-s-85 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Ff-s-85 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

### **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/MS51100-37">https://military-fasteners.com/bolts/machine+bolts/MS51100-37</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.