

Description

MS51552L06 NUT,SELF-LOCKING,PLATE

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS51552L06
Minimum Qty (MOQ):	5
NSN:	5310-01-309-4791
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS51552L06 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.684 Inches Maximum
Distance From Base To Center Of Aperture:	0.165 Inches Minimum And 0.175 Inches Maximum
Nut Height:	0.170 Inches Maximum
Plate Thickness:	0.020 Inches Minimum And 0.035 Inches Maximum
Plate Width:	0.325 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Mounting Hole Center To Base:	0.320 Inches Minimum And 0.330 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.217 Inches Minimum And 0.221 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.138 Inches
Material:	Steel Comp 1035 Overall Or Steel Comp 1040 Overall Or Steel Comp 1050 Overall Or Steel Comp 4130 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Astm A29 Assn Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS51552L06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.