

Description

MS51576-11 Shoulder Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS5157611
Minimum Qty (MOQ):	5
NSN:	5305-01-332-8348
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

P/N MS51576-11 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.1563 Inches Minimum And 0.2187 Inches Maximum
Fastener Length:	0.2063 Inches Minimum And 0.2690 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.2813 Inches Minimum And 0.3437 Inches Maximum
Head Height:	0.1250 Inches Minimum And 0.1874 Inches Maximum
Shoulder Diameter:	0.1860 Inches Minimum First Shoulder And 0.1870 Inches Maximum First Shoulder
Shoulder Length:	0.500 Inches Minimum First Shoulder And 0.503 Inches Maximum First Shoulder
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.0940 Inches Nominal
Thread Quantity Per Inch:	32
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 303 Overall
Material Document And Classification:	Astm A582 Cond. A Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this shoulder screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51576-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.