

**Description**

MS51576-3 Shoulder Screw

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS515763
Minimum Qty (MOQ):	10
NSN:	5305-01-328-1684
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE  
AVAILABLE

## P/N MS51576-3 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.125 Inches Minimum And 0.187 Inches Maximum
<b>Fastener Length:</b>	0.375 Inches Minimum And 0.440 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.218 Inches Minimum And 0.281 Inches Maximum
<b>Head Height:</b>	0.093 Inches Minimum And 0.156 Inches Maximum
<b>Shoulder Diameter:</b>	0.123 Inches Minimum First Shoulder And 0.124 Inches Maximum First Shoulder
<b>Shoulder Length:</b>	0.250 Inches Minimum First Shoulder And 0.253 Inches Maximum First Shoulder
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Width Across Flats:</b>	0.078 Inches Nominal
<b>Thread Quantity Per Inch:</b>	40
<b>Hardness Rating:</b>	32.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
<b>Shoulder Shape:</b>	Round First Shoulder
<b>Material:</b>	Steel Comp Xm-7 Overall Or Steel Comp 303 Overall
<b>Material Document And Classification:</b>	Astm A493 Assn Std 1st Material Response Overall Or Astm A582 Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this shoulder screw from our inventory online by visiting <https://military-fasteners.com/screws/screw/MS51576-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.