

Description

MS51576-3 Shoulder Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS515763 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-328-1684 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS51576-3 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.125 Inches Minimum And 0.187 Inches Maximum |
| Fastener Length: | 0.375 Inches Minimum And 0.440 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.218 Inches Minimum And 0.281 Inches Maximum |
| Head Height: | 0.093 Inches Minimum And 0.156 Inches Maximum |
| Shoulder Diameter: | 0.123 Inches Minimum First Shoulder And 0.124 Inches Maximum First Shoulder |
| Shoulder Length: | 0.250 Inches Minimum First Shoulder And 0.253 Inches Maximum First Shoulder |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.112 Inches |
| Width Across Flats: | 0.078 Inches Nominal |
| Thread Quantity Per Inch: | 40 |
| Hardness Rating: | 32.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall |
| Shoulder Shape: | Round First Shoulder |
| Material: | Steel Comp Xm-7 Overall Or Steel Comp 303 Overall |
| Material Document And Classification: | Astm A493 Assn Std 1st Material Response Overall Or Astm A582 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this shoulder screw from our inventory online by visiting <https://military-fasteners.com/screws/screw/MS51576-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.