

Description

MS51576-5 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS515765
Minimum Qty (MOQ):	10
NSN:	5305-01-433-8464
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N MS51576-5 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.125 Inches Minimum And 0.187 Inches Maximum
Fastener Length:	0.687 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.281 Inches Maximum
Head Height:	0.093 Inches Minimum And 0.156 Inches Maximum
Shoulder Diameter:	0.1235 Inches Minimum First Shoulder And 0.1245 Inches Maximum First Shoulder
Shoulder Length:	0.372 Inches Minimum First Shoulder And 0.378 Inches Maximum First Shoulder
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.112 Inches
Width Across Flats:	0.078 Inches Nominal
Thread Quantity Per Inch:	40
Hardness Rating:	32.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp Xm-7 Overall Or Steel Comp 303 Overall
Material Document And Classification:	Astm A493 Assn Std 1st Material Response Overall Or Astm A582 Assn Std 2nd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51576-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.