

P/N MS51576-9

Description

Fastener Length: 1/2", Thread: 8-32, Head Width: 3/32", Thread Length: 3/16

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS515769

Minimum Qty (MOQ): 5

NSN: 5305-01-019-2483

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS51576-9 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.188 Inches Nominal
Fastener Length:	0.501 Inches Minimum And 0.503 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.312 Inches Nominal
Head Height:	0.156 Inches Nominal
Shoulder Diameter:	0.186 Inches Minimum First Shoulder And 0.188 Inches Maximum First Shoulder
Shoulder Length:	0.313 Inches Minimum First Shoulder And 0.316 Inches Maximum First Shoulder
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.094 Inches Nominal
Thread Quantity Per Inch:	32
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 303 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS51576-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.