


**Description**

Thread Size: 3/8", MS51830 series insert

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS51830CA204L
Minimum Qty (MOQ):	2
NSN:	5325-01-070-6527
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N MS51830CA204L Specifications

<b>Thread Class:</b>	3b
<b>Length:</b>	0.485 Inches Minimum And 0.515 Inches Maximum
<b>Insert Size:</b>	0.500-13 Unc-2a
<b>Internal Thread Relief Depth:</b>	0.060 Inches Minimum And 0.080 Inches Maximum
<b>Full Internal Thread Length:</b>	0.405 Inches Minimum And 0.455 Inches Maximum
<b>Features Provided:</b>	Individually Keyed
<b>Thread Quantity Per Inch:</b>	24
<b>Nominal Thread Size:</b>	0.375 Inches
<b>Special Features:</b>	Dry Film Lubricant Mil-I-8937
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Grooved Keylock
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/MS51830CA204L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.