

Description

Thread Size: 3/16", Thread Length: 19/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[NAS1395-3L](#)

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS51831A201L |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5325-00-948-9834 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N MS51831A201L Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Thread Length: | 0.297 Inches Minimum And 0.327 Inches Maximum |
| Length: | 0.297 Inches Minimum And 0.327 Inches Maximum |
| Insert Size: | 3/8-16 Unc 2a |
| Internal Thread Relief Depth: | 0.070 Inches Nominal |
| Full Internal Thread Length: | 0.240 Inches Nominal |
| Features Provided: | Individually Keyed |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Material: | Steel Comp 303 Overall Or Steel Comp 303se Overall |
| Material Document And Classification: | Ams 5640 (uns S30300)type I Assn Std 1st Material Response Overall And Ams 5640 (uns S30323)type II Assn Std 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall |
| Style Designator: | Grooved Keylock |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1395 Professional/industrial Association Standard |

How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/MS51831A201L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.