

Description

Thread Size: 1/4", Thread Length: 1/4", stainless steel, dry film lubricant, MS51831 series insert

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[NAS1395CA4L](#)

SKU / Model:	MS51831CA202L
Minimum Qty (MOQ):	2
NSN:	5325-01-113-0927
Schedule B:	7318.16.0060
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS51831CA202L Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Thread Length:	0.305 Inches Nominal
Length:	0.360 Inches Minimum And 0.390 Inches Maximum
Insert Size:	7/16-14 Unc 2a
Internal Thread Relief Depth:	0.060 Inches Minimum And 0.080 Inches Maximum
Full Internal Thread Length:	0.280 Inches Minimum And 0.330 Inches Maximum
Features Provided:	Individually Keyed
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Special Features:	Dry Film Lubricant. Has Internal Thread Lock
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5734 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Keylock
Thread Series Designator:	Unjf

How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/MS51831CA202L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.