

**Description**

Thread Size: 1/4", Thread Length: 1/4", stainless steel, dry film lubricant, MS51831 series insert

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[NAS1395CA4L](#)

SKU / Model:	MS51831CA202L
Minimum Qty (MOQ):	2
NSN:	5325-01-113-0927
Schedule B:	7318.16.0060
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N MS51831CA202L Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.305 Inches Nominal
<b>Length:</b>	0.360 Inches Minimum And 0.390 Inches Maximum
<b>Insert Size:</b>	7/16-14 Unc 2a
<b>Internal Thread Relief Depth:</b>	0.060 Inches Minimum And 0.080 Inches Maximum
<b>Full Internal Thread Length:</b>	0.280 Inches Minimum And 0.330 Inches Maximum
<b>Features Provided:</b>	Individually Keyed
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Special Features:</b>	Dry Film Lubricant. Has Internal Thread Lock
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams 5734 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Keylock
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/MS51831CA202L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.