

Description

Thread Size: 5/16", Thread Length: 23/64", dry film lubricant, MS51831 series insert

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS51831CA203L
Minimum Qty (MOQ):	5
NSN:	5325-01-113-0926
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS51831CA203L Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Thread Length:	0.367 Inches Nominal
Length:	0.422 Inches Minimum And 0.452 Inches Maximum
Insert Size:	1/2-13 Unc 2a
Internal Thread Relief Depth:	0.060 Inches Minimum And 0.080 Inches Maximum
Full Internal Thread Length:	0.342 Inches Minimum And 0.392 Inches Maximum
Features Provided:	Individually Keyed
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.3125 Inches
Special Features:	Dry Film Lubricant. Item Has Internal Thread Lock Feature.
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5734 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Keylock
Thread Series Designator:	Unjf

How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/MS51831CA203L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.