

Description

Fastener Length: 1-1/4", Thread: 1/4-24, Thread Length: 1-1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS51849109
Minimum Qty (MOQ):	20
NSN:	5305-01-121-0332
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS51849-109 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.107 Inches Minimum And 1.250 Inches Maximum
Fastener Length:	1.190 Inches Minimum And 1.250 Inches Maximum
Head Style:	Hexagon
Head Height:	0.208 Inches Minimum And 0.230 Inches Maximum
Width Between Flats:	0.489 Inches Minimum And 0.500 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel Comp 1109 Or Steel Comp 1110 Or Steel Comp 1116 Or Steel Comp 1117 Or Steel Comp 1118 Or Steel Comp 1119 Or Steel Comp 1132 Or Steel Comp 1137 Or Steel Comp 1140 Or Steel Comp 1141 Or Steel Comp 1144 Or Steel Comp 1145 Or Steel Comp 1146 Or Steel Comp 1151 Or Steel Comp 1211 Or Steel Comp 1212 Or Steel Comp 1213 Or Steel Comp 1215 Or Steel Comp 1214 Or Steel Comp 1139
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response Or Mil-c-81562,ty 2 Cl 3 Mil Spec Single Treatment Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 10s Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51849-109> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.