

Description

Fastener Length: 1/4", Thread: 4-40, Thread Length: 1/4", MS51849 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5184911C
Minimum Qty (MOQ):	100
NSN:	5305-01-373-8818
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS51849-11C Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.250 Inches Maximum
Fastener Length:	0.220 Inches Minimum And 0.250 Inches Maximum
Head Style:	Hexagon
Head Height:	0.049 Inches Minimum And 0.060 Inches Maximum
Width Between Flats:	0.181 Inches Minimum And 0.187 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 303se Or Steel Comp 304 Or Steel Comp 304l Or Steel Comp 305 Or Steel Comp 309 Or Steel Comp 310 Or Steel Comp 316 Or Steel Comp 316l Or Steel Comp 317 Or Steel Comp 321 Or Steel Comp 347
Screw Material Document And Classification:	Qq-s-763 Fed Spec All Material Responses Or Fed-std66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Astm A380 Assn Std Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51849-11C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.