

**Description**

Fastener Length: 19/64", Thread: 4-40, Thread Length: 19/64", MS51849 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS5184912
Minimum Qty (MOQ):	100
NSN:	5305-01-005-3181
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS51849-12 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.230 Inches Minimum And 0.310 Inches Maximum
<b>Fastener Length:</b>	0.280 Inches Minimum And 0.310 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.049 Inches Minimum And 0.060 Inches Maximum
<b>Width Between Flats:</b>	0.181 Inches Minimum And 0.187 Inches Maximum
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	60000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel
<b>Screw Material Document And Classification:</b>	Fed Std 66 Fed Std Single Material Response
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2 Cl 3 Fed Spec All Treatment Responses
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	1 Type And 10s Style

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51849-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.