

P/N MS51849-12

Description

Fastener Length: 19/64", Thread: 4-40, Thread Length: 19/64", MS51849 series screw

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS5184912

Minimum Qty (MOQ): 100

NSN: 5305-01-005-3181

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS51849-12 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.230 Inches Minimum And 0.310 Inches Maximum
Fastener Length:	0.280 Inches Minimum And 0.310 Inches Maximum
Head Style:	Hexagon
Head Height:	0.049 Inches Minimum And 0.060 Inches Maximum
Width Between Flats:	0.181 Inches Minimum And 0.187 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Fed Std 66 Fed Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Type And 10s Style

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS51849-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS51849-12 and selecting the quantity you