

Description

Fastener Length: 25/64", Thread: 4-40, Thread Length: 25/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5184913C
Minimum Qty (MOQ):	25
NSN:	5305-01-366-5698
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS51849-13C Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.335 Inches Minimum And 0.390 Inches Maximum
Fastener Length:	0.385 Inches Minimum And 0.390 Inches Maximum
Head Style:	Hexagon
Head Height:	0.049 Inches Minimum And 0.060 Inches Maximum
Width Between Flats:	0.181 Inches Minimum And 0.187 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 303ma Or Steel Comp 303pb Or Steel Comp 303 Plus X Or Steel Comp 303se Or Steel Comp 416 Or Steel Comp 416 Plus X Or Steel Comp 416se Or Steel Comp 420f Or Steel Comp 420fse Or Steel Comp 430f Or Steel Comp 430fse Or Steel Comp 440f Or Steel Comp 440fse
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Type And 10 Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51849-13C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.