

**Description**

Fastener Length: 19/64", Thread: 6-32, Thread Length: 19/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS5184932
Minimum Qty (MOQ):	200 EA
NSN:	5305-01-030-8753
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS51849-32 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.218 Inches Minimum And 0.310 Inches Maximum
<b>Fastener Length:</b>	0.280 Inches Minimum And 0.310 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.080 Inches Minimum And 0.093 Inches Maximum
<b>Width Between Flats:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	60000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel
<b>Screw Material Document And Classification:</b>	Qq-s-637 Fed Spec 1st Material Response Or Fed Std 66 Fed Std 2nd Material Response
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec 1st Treatment Response Or Mil-c-81562 Ty 2 Cl 3 Mil Spec 2nd Treatment Response
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	1 Type And 10s Style

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51849-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.