

Description

Fastener Length: 1/2", Thread: 10-32, Thread Length: 1/2",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5184964C
Minimum Qty (MOQ):	25
NSN:	5305-01-367-1294
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS51849-64C Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.500 Inches Nominal
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.312 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 309 Or Steel Comp 310 Or Steel Comp 316
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec 1st Treatment Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1,sty 10 Type

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51849-64C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.