

Description

Fastener Length: 1-1/4", Thread: 10-32, Thread Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS5184969 |
| Minimum Qty (MOQ): | 95 EA |
| NSN: | 5305-01-090-6320 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS51849-69 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.128 Inches Minimum And 1.250 Inches Maximum |
| Fastener Length: | 1.190 Inches Minimum And 1.250 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.105 Inches Minimum And 0.120 Inches Maximum |
| Width Between Flats: | 0.305 Inches Minimum And 0.312 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Screw Material: | Steel |
| Screw Material Document And Classification: | Qq-s-637 Fed Spec Single Material Response Or 66 Fed Std Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Or Mil-c-81562 Ty 2 Cl 3 Mil Spec Single Treatment Response |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | 1 Type And 10s Style |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51849-69> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.