

Description

Fastener Length: 1-1/4", Thread: 10-32, Thread Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5184969
Minimum Qty (MOQ):	95 EA
NSN:	5305-01-090-6320
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS51849-69 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.128 Inches Minimum And 1.250 Inches Maximum
Fastener Length:	1.190 Inches Minimum And 1.250 Inches Maximum
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.312 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-637 Fed Spec Single Material Response Or 66 Fed Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Or Mil-c-81562 Ty 2 Cl 3 Mil Spec Single Treatment Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 10s Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51849-69> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.