

P/N MS51849-95

Military-Fasteners.com

Description

Fastener Length: 39/64", Thread: 1/4-20, Thread Length: 39/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS5184995
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-016-4344
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS51849-95 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.490 Inches Minimum And 0.620 Inches Maximum
Fastener Length:	0.590 Inches Minimum And 0.620 Inches Maximum
Head Style:	Hexagon
Head Height:	0.172 Inches Minimum And 0.190 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.375 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	66 Fed Std Single Material Response Or Qq-s-637 Fed Spec Single Material Response Or Astm A108 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Or Mil-c-81562 Ty 2 Cl 3 Mil Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Type And 10s Style

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/MS51849-95</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.