

Description

Fastener Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS5185043
Minimum Qty (MOQ):	75 EA
NSN:	5305-00-151-6136
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS51850-43 Specifications

Fastener Length:	0.350 Inches Minimum And 0.410 Inches Maximum
Head Style:	Hexagon
Head Height:	0.096 Inches Minimum And 0.110 Inches Maximum
Width Between Flats:	0.244 Inches Minimum And 0.250 Inches Maximum
Internal Drive Style:	Slot
End Item Identification:	W/s: Helicopter, Uscg Search And Rescue, Hh-60j; Field Artillery Ammunition Support Vehicle (faagv) (m992); Helicopter, Carrier Based Asw, Sh-60f; Aircraft, Prowler Ea-6b; Helicopter, Advance Attack, Ah-1w; Helicopter, Search And Rescue, Hh-60h; Recovery Vehicle, Full-tracked Medium, W/e (m88a1); Helicopter, Mh-53e; Aircraft, C-2a (reprocured); Helicopter, Seahawk, H-60
Features Provided:	Casehardened
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Nonmachine Nominal Thread Diameter:	0.164 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	Ab Type

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51850-43> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.