

Description

Length: 3/8", thread: 4-24, pan head, stainless steel, MS51861 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5186114C
Minimum Qty (MOQ):	100
NSN:	5305-00-163-6561
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS51861-14C Specifications

Fastener Length:	0.344 Inches Minimum And 0.406 Inches Maximum
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s: Wasp Class Lhd; Aircraft, Prowler Ea-6b; Aircraft, B-2 Bomber (atb); Nimitz Class Cvn; Emory S. Land Class As; General Purpose Electronic Test Equipment Gpete; Landing Craft Air Cushion (Lcac); Fms-know Class Ff; Forrestal Class Cv; Support Equipment, B-1 Aircraft
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Nonmachine Nominal Thread Diameter:	0.112 Inches
Material:	Steel Comp 410 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	Ab Type

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51861-14C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.