

**Description**


length: 1/2, thread: 4-24, pan head tapping screw type a point

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS5186115
Minimum Qty (MOQ):	100
NSN:	5305-00-053-1114
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS51861-15 Specifications

<b>Fastener Length:</b>	0.469 Inches Minimum And 0.500 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.205 Inches Minimum And 0.219 Inches Maximum
<b>Head Height:</b>	0.070 Inches Minimum And 0.080 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>End Item Identification:</b>	W/s:shop Equipment, General Purpose Repair, Trlr, Semi-mounted; Shop Equipment, Organizational Repair, Light, Truck-mounted; Defense Communications Radio (9 Sytems); Radar Set, Lightweight 3d (an/tps-59); Aircraft, T-39; Helicopter, Mh-53e; Helicopter, Advance Attack, Ah-1w; Helicopter, Carrier Based Asw, Sh-60f; Aircraft, C-2a (reprocured); Consolidated Targets
<b>Features Provided:</b>	Casehardened
<b>Nonmachine Thread Style:</b>	Dog Type (type B Or C)
<b>Nonmachine Nominal Thread Diameter:</b>	0.112 Inches
<b>Material:</b>	Steel Comp 1016 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1524 Overall
<b>Material Document And Classification:</b>	Aisi Assn Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall

## How to Order

Order this tapping screw from our inventory online by visiting <https://military-fasteners.com/screws/tapping+screws/MS51861-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.