

**Description**

length: 1/2", thread: 4-24, pan head, tapping style, corrosion resistant steel, type a point

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS5186115C
Minimum Qty (MOQ):	100
NSN:	5305-00-147-3224
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS51861-15C Specifications

<b>Fastener Length:</b>	0.469 Inches Minimum And 0.531 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.205 Inches Minimum And 0.219 Inches Maximum
<b>Head Height:</b>	0.070 Inches Minimum And 0.080 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>End Item Identification:</b>	W/s: Intermediate Forward Test Equip (ifte) System; Wasp Class Lhd; Supply Class Aoe; Trainer, B-1b Aircraft; Nimitz Class Cvn; Radar Set, Lightweight 3d (an/tps-59); Forrestal Class Cv; Ground Mobile Force Satellite Comm Term (an/tsc-93a); Support Equipment, B-1 Aircraft; Spruance Class Dd (963)
<b>Nonmachine Thread Style:</b>	Gimlet Point (type A, Ab Or Ba)
<b>Nonmachine Nominal Thread Diameter:</b>	0.112 Inches
<b>Material:</b>	Steel Comp 410 Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Nondefinitive Spec/std Data:</b>	Ab Type

## How to Order

Order this tapping screw from our inventory online by visiting <https://military-fasteners.com/screws/tapping+screws/MS51861-15C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.