

Description

length: 1/2", thread: 4-24, pan head, tapping style, corrosion resistant steel, type a point

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS5186115C |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-147-3224 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS51861-15C Specifications

| | |
|---|---|
| Fastener Length: | 0.469 Inches Minimum And 0.531 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.205 Inches Minimum And 0.219 Inches Maximum |
| Head Height: | 0.070 Inches Minimum And 0.080 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| End Item Identification: | W/s: Intermediate Forward Test Equip (ifte) System; Wasp Class Lhd; Supply Class Aoe; Trainer, B-1b Aircraft; Nimitz Class Cvn; Radar Set, Lightweight 3d (an/tps-59); Forrestal Class Cv; Ground Mobile Force Satellite Comm Term (an/tsc-93a); Support Equipment, B-1 Aircraft; Spruance Class Dd (963) |
| Nonmachine Thread Style: | Gimlet Point (type A, Ab Or Ba) |
| Nonmachine Nominal Thread Diameter: | 0.112 Inches |
| Material: | Steel Comp 410 Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Nondefinitive Spec/std Data: | Ab Type |

How to Order

Order this tapping screw from our inventory online by visiting <https://military-fasteners.com/screws/tapping+screws/MS51861-15C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.