

**Description**

Length: 3/8", Thread: 6-20, pan head, type A point, corrosion resistant steel, MS51861 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS5186124C
Minimum Qty (MOQ):	100
NSN:	5305-00-147-3228
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS51861-24C Specifications

<b>Fastener Length:</b>	0.344 Inches Minimum And 0.406 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.256 Inches Minimum And 0.270 Inches Maximum
<b>Head Height:</b>	0.087 Inches Minimum And 0.097 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>End Item Identification:</b>	W/s: Missile, Air-to-air, Phoenix (aim-54); Support Equipment, B-1 Aircraft; Helicopter, Carrier Based Asw, Sh-60f; Aircraft, Airlifter C-17a; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Helicopter, Search And Rescue, Hh-60h; Helicopter, Advance Attack, Ah-1w; Helicopter, Mh-53e; Defense Meteorological Satellite Program (dmisp)
<b>Nonmachine Thread Style:</b>	Gimlet Point (type A, Ab Or Ba)
<b>Nonmachine Nominal Thread Diameter:</b>	0.138 Inches
<b>Material:</b>	Steel Comp 410 Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Nondefinitive Spec/std Data:</b>	Ab Type

## How to Order

Order this tapping screw from our inventory online by visiting <https://military-fasteners.com/screws/tapping+screws/MS51861-24C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.