

Description

Length: 3/8", Thread: 6-20, pan head, type A point, corrosion resistant steel, MS51861 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5186124C
Minimum Qty (MOQ):	100
NSN:	5305-00-147-3228
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS51861-24C Specifications

Fastener Length:	0.344 Inches Minimum And 0.406 Inches Maximum
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s: Missile, Air-to-air, Phoenix (aim-54); Support Equipment, B-1 Aircraft; Helicopter, Carrier Based Asw, Sh-60f; Aircraft, Airlifter C-17a; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Helicopter, Search And Rescue, Hh-60h; Helicopter, Advance Attack, Ah-1w; Helicopter, Mh-53e; Defense Meteorological Satellite Program (dmosp)
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Nonmachine Nominal Thread Diameter:	0.138 Inches
Material:	Steel Comp 410 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	Ab Type

How to Order

Order this tapping screw from our inventory online by visiting <https://military-fasteners.com/screws/tapping+screws/MS51861-24C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.