

## P/N MS51861-27

### **Description**

length: 3/4", thread: 6-20, pan head tapping screw type a point"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS5186127

Minimum Qty (MOQ): 100

NSN: 5305-00-432-4166

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS51861-27 Specifications

Fastener Length:	0.719 Inches Minimum And 0.781 Inches Maximum
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Features Provided:	Casehardened
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Nonmachine Nominal Thread Diameter:	0.138 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	Ab Type

# **How to Order**

Order this tapping screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/tapping+screws/MS51861-27">https://military-fasteners.com/screws/tapping+screws/MS51861-27</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/tapping+screws/MS51861-27">https://military-fasteners.com/screws/tapping+screws/MS51861-27</a> and selecting the quantity you