



Military-Fasteners.com

P/N MS51861-34C

Description

length: 3/8", thread: 8-18, pan head tapping screw - corrosion resistant steel - type a point

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5186134C
Minimum Qty (MOQ):	100
NSN:	5305-00-139-6757
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS51861-34C Specifications

Fastener Length:	0.344 Inches Minimum And 0.406 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Nonmachine Nominal Thread Diameter:	0.164 Inches
Material:	Steel Comp 410 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	Ab Type

How to Order

Order this tapping screw from our inventory online by visiting <https://military-fasteners.com/screws/tapping+screws/MS51861-34C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.