

P/N MS51861-35C

Description

length: 1/2", thread: 8-18, pan head tapping screw, corrosion resistant steel, type a point

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS5186135C

Minimum Qty (MOQ): 100

NSN: 5305-00-433-3711

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS51861-35C Specifications

Fastener Length:	0.469 Inches Minimum And 0.531 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Nonmachine Nominal Thread Diameter:	0.164 Inches
Material:	Steel Comp 410 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	Ab Type

How to Order

Order this tapping screw from our inventory online by visiting https://military-fasteners.com/screws/tapping+screws/MS51861-35C and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/tapping+screws/MS51861-35C and selecting the quantity you