

Description

length: 5/8", thread: 8-18, pan head, tapping type, type a point

* Manufacturer certifications are shipped with your order FREE of charge


Order this part online

Additional Information

Alternate Part Numbers

[AN530-8R10](#)

SKU / Model:	MS5186136
Minimum Qty (MOQ):	100
NSN:	5305-00-432-4171
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS51861-36 Specifications

Fastener Length:	0.594 Inches Minimum And 0.656 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Features Provided:	Casehardened
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Nonmachine Nominal Thread Diameter:	0.164 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	Ab Type

How to Order

Order this tapping screw from our inventory online by visiting <https://military-fasteners.com/screws/tapping+screws/MS51861-36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.