

Description

length: 1/2, thread: 10-16, pan head, type a point

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS5186145 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-01-295-0089 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS51861-45 Specifications

| | |
|--|---|
| Fastener Length: | 0.469 Inches Minimum And 0.531 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.357 Inches Minimum And 0.373 Inches Maximum |
| Head Height: | 0.122 Inches Minimum And 0.133 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Features Provided: | Casehardened |
| Nonmachine Thread Style: | Gimlet Point (type A, Ab Or Ba) |
| Nonmachine Nominal Thread Diameter: | 0.190 Inches |
| Material: | Steel Comp 1016 Overall Or Steel Comp 1017 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1020 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1023 Overall Or Steel Comp 1524 Overall |
| Material Document And Classification: | Aisi Assn Std Single Material Response Overall |
| Surface Treatment: | Zinc Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Astm B633 Ty 2 Cl Fe/zn 13 Assn Std Single Treatment Response Overall |
| Nondefinitive Spec/std Data: | Ab Type |
| Departure From Cited Document: | As Differentiated By Surface |

How to Order

Order this tapping screw from our inventory online by visiting <https://military-fasteners.com/screws/tapping+screws/MS51861-45> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.