

P/N MS51861-45

Military-Fasteners.com

Description

length: 1/2, thread: 10-16, pan head, type a point

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS5186145
Minimum Qty (MOQ):	100
NSN:	5305-01-295-0089
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS51861-45 Specifications

Fasteney Lewith.	0.400 la shee Minimure And 0.521 la shee Meujeuure	
Fastener Length:	0.469 Inches Minimum And 0.531 Inches Maximum	
Head Style:	Pan	
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum	
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum	
Internal Drive Style:	Cross Recess Type 1	
Features Provided:	Casehardened	
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)	
Nonmachine Nominal Thread Diameter:	0.190 Inches	
Material:	Steel Comp 1016 Overall Or Steel Comp 1017 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1020 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1023 Overall Or Steel Comp 1524 Overall	
Material Document And Classification:	Aisi Assn Std Single Material Response Overall	
Surface Treatment:	Zinc Overall And Chromate Overall	
Surface Treatment Document And Classification:	Astm B633 Ty 2 Cl Fe/zn 13 Assn Std Single Treatment Response Overall	
Nondefinitive Spec/std Data:	Ab Type	
Departure From Cited Document:	As Differentiated By Surface	

How to Order

Order this tapping screw from our inventory online by visiting <u>https://military-fasteners.com/screws/tapping+screws/MS51861-45</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.