

Description

length: 1/2", thread: 10-16, pan head tapping screw, corrosion resistant steel, type a point

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5186145C
Minimum Qty (MOQ):	100
NSN:	5305-00-147-3238
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS51861-45C Specifications

Fastener Length:	0.469 Inches Minimum And 0.531 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s: Spruance Class Dd (963); Arleigh Burke Class Ddg; Support Equip, C-17a Aircraft; Consolidated Space Operations Center; An/sqq-89 Surface Ship Asw Combat System; Support Equipment, B-52 Aircraft; Armored Security Vehicle, Modle Xm1117; Low Altitude Navigation & Targeting Infrared System (Iantirn); Truck, Fire/crash P10
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Nonmachine Nominal Thread Diameter:	0.190 Inches
Material:	Steel Comp 410 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	Ab Type

How to Order

Order this tapping screw from our inventory online by visiting <https://military-fasteners.com/screws/tapping+screws/MS51861-45C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.