

P/N MS51861-48

Military-Fasteners.com

Description

length: 7/8", thread: 10-16, pan head, tapping, type a point

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS5186148
Minimum Qty (MOQ):	100
NSN:	5305-00-432-4204
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS51861-48 Specifications

Fastener Length:	0.844 Inches Minimum And 0.906 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Features Provided:	Casehardened
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Nonmachine Nominal Thread Diameter:	0.190 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	Ab Type

How to Order

Order this tapping screw from our inventory online by visiting <u>https://military-fasteners.com/screws/tapping+screws/MS51861-48</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.