

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS5186212 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-01-028-4831 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS51862-12 Specifications

| | |
|---|--|
| Fastener Length: | 0.281 Inches Minimum And 0.343 Inches Maximum |
| Head Style: | Flat Countersunk Undercut |
| Head Diameter: | 0.244 Inches Minimum And 0.279 Inches Maximum |
| Head Height: | 0.048 Inches Minimum And 0.059 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Features Provided: | Casehardened |
| Nonmachine Thread Style: | Gimlet Point (type A, Ab Or Ba) |
| Countersink Angle: | 81.0 Degrees Nominal |
| Nonmachine Nominal Thread Diameter: | 0.138 Inches |
| Material: | Steel Comp 1016 Overall Or Steel Comp 1018 Overall Or Steel Comp 1022 Overall Or Steel Comp 1022 Overall Or Steel Comp 1019 Overall Or Steel Comp 1524 Overall |
| Material Document And Classification: | Aisi Assn Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall |
| Nondefinitive Spec/std Data: | Ab Type |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51862-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.