

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5186212
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-028-4831
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS51862-12 Specifications

Fastener Length:	0.281 Inches Minimum And 0.343 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.244 Inches Minimum And 0.279 Inches Maximum
Head Height:	0.048 Inches Minimum And 0.059 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Features Provided:	Casehardened
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Countersink Angle:	81.0 Degrees Nominal
Nonmachine Nominal Thread Diameter:	0.138 Inches
Material:	Steel Comp 1016 Overall Or Steel Comp 1018 Overall Or Steel Comp 1022 Overall Or Steel Comp 1022 Overall Or Steel Comp 1019 Overall Or Steel Comp 1524 Overall
Material Document And Classification:	Aisi Assn Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Nondefinitive Spec/std Data:	Ab Type

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51862-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.