

## Description

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS5186212C
Minimum Qty (MOQ):	25 EA
NSN:	5305-01-058-3890
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS51862-12C Specifications

<b>Fastener Length:</b>	0.281 Inches Minimum And 0.343 Inches Maximum
<b>Head Style:</b>	Flat Countersunk Undercut
<b>Head Diameter:</b>	0.244 Inches Minimum And 0.279 Inches Maximum
<b>Head Height:</b>	0.048 Inches Minimum And 0.059 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nonmachine Thread Style:</b>	Gimlet Point (type A, Ab Or Ba)
<b>Countersink Angle:</b>	81.0 Degrees Nominal
<b>Nonmachine Nominal Thread Diameter:</b>	0.138 Inches
<b>Material:</b>	Steel Comp 410 Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Nondefinitive Spec/std Data:</b>	Ab Type

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51862-12C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.