

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5186213
Minimum Qty (MOQ):	95 EA
NSN:	5305-00-432-4387
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS51862-13 Specifications

Fastener Length:	0.344 Inches Minimum And 0.406 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.244 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Features Provided:	Casehardened
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Nonmachine Nominal Thread Diameter:	0.138 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	Ab Type

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51862-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.