

Description

length: 3/8", thread: 6-20, flat head 82°, tapping screw - corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS5186213C |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-052-8893 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS51862-13C Specifications

| | |
|--|--|
| Fastener Length: | 0.344 Inches Minimum And 0.406 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.244 Inches Minimum And 0.279 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nonmachine Thread Style: | Gimlet Point (type A, Ab Or Ba) |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Nonmachine Nominal Thread Diameter: | 0.138 Inches |
| Material: | Steel Comp 410 Overall Or Steel Comp 420 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |

How to Order

Order this tapping screw from our inventory online by visiting <https://military-fasteners.com/screws/tapping+screws/MS51862-13C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.