

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS5186215 |
| Minimum Qty (MOQ): | 60 EA |
| NSN: | 5305-00-432-4389 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS51862-15 Specifications

| | |
|---|--|
| Fastener Length: | 0.594 Inches Minimum And 0.656 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.244 Inches Minimum And 0.279 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Features Provided: | Casehardened |
| Nonmachine Thread Style: | Gimlet Point (type A, Ab Or Ba) |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Nonmachine Nominal Thread Diameter: | 0.138 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall |
| Nondefinitive Spec/std Data: | Ab Type |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51862-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.