

Description

Fastener Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS5186223C
Minimum Qty (MOQ):	20 EA
NSN:	5305-01-059-1931
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS51862-23C Specifications

Fastener Length:	0.344 Inches Minimum And 0.406 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.292 Inches Minimum And 0.332 Inches Maximum
Head Height:	0.058 Inches Minimum And 0.070 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Countersink Angle:	81.0 Degrees Nominal
Nonmachine Nominal Thread Diameter:	0.164 Inches
Material:	Steel Comp 410 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	Ab Type

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51862-23C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.